

Extreme Temperature Pressure Sensor



Features

- ➔ All Stainless steel
- ➔ Miniature pressure sensor
- ➔ Optional remote electronic
- ➔ Operating from -20 to +250°C

Applications

- ➔ Oil & gas
- ➔ Aerospace
- ➔ Military
- ➔ Test benches

Operating up to 250°C, PET160 is a ruggedized pressure sensor dedicated to extreme temperature. With all stainless steel wetted parts, It is compatible with most media, including corrosive fluids used in automotive and aerospace industries. Equipped with the latest thin film technology developed by EFE, its performances and stability over wide temperature range are excellent. Models are available with unamplified and voltage outputs, thanks to a remote electronic module, packaged in a miniature stainless steel housing, fitted in the cable and operating up to 125°C.

Technical specifications


Pressure ranges (FS)	20bar ; 40bar ; 100bar ; 250bar ; 400bar ; 600bar ; 300PSI ; 500PSI ; 1500PSI ; 3000PSI ; 10000PSI ; 5000PSI
Type	Gage
Safe overload	150% FS
Burst pressure	300% FS
Output impedance	> 3000 Ohms typ.
Input impedance	> 3500 Ohms typ.
Power supply	5 to 15Vdc
Consumption	< 10mA
Insulation	> 1000 MOhms under 50Vdc at ambient temperature
Output at 0%FS	0mV/V
Output at 100%FS	1 to 2mV/V
Zero and sensitivity settings tolerances	±3% FS
Non linearity and hysteresis combined	±0.25% FS
Non repeatability	±0.02% FS typ.

Technical Specifications



Compensated temperature range	+20 to +250°C
Operating temperature range	-20 to +250°C
Combined thermal zero & sensitivity shifts	±0.03% FS/°C
Constant acceleration in linear vibrations	± 0.02% FS/g (frequency 20-2000Hz, 50g max.)
Mechanical shock	100g ½ sinus 1ms
Electrical protection	Protected against polarity inversion
EMC protection	Compliant to EN61000
Electrical connection	AWG26 Shielded Teflon Cable Ø3.4mm ±0.2, 5 wires
Mechanical connection	M10x1-4h male Option : 3/8-24 UNF-3A male
Material(s) of wetted parts	Stainless Steel 316L ; Stainless Steel 17-4PH ; Stainless steel 15-5PH
Weight	< 40g without cable
Enclosure protection	IP65 for absolute & sealed gage version

Codification

Extreme Temperature Pressure Sensor	PET16	1	S	40bar	G	02	09/1m	H	1	3
Output Signal										
	mV/V	1								
Material										
	Stainless Steels		S							
Range										
	Example			40bar						
Type										
	Gage				G					
Mechanical connection										
	M10x1-4h male					02				
	3/8-24 UNF-3A male					11				
Electrical connection										
	AWG26 Shielded Teflon Cable Ø3.4mm ±0.2, 5 wires						09/1m			
Compensated temperature range										
	+20 to +250°C							H		
Non linearity and hysteresis combined										
	±0.25% FS								1	
Combined thermal zero & sensitivity shifts										
	±0.03% FS/°C									3



Dimensions : mm

5 CONDUCTOR TEFLON CABLE		
mV/V OUTPUT	CONDUCTOR	
+ EXCITATION	RED	
+ SIGNAL	GREEN	
- SIGNAL	WHITE	
- EXCITATION	BLACK	
NC	BLUE	
SENSOR HOUSING	SHIELD	

Agent :



E.F.E.

L'ESSOR FRANCAIS ELECTRONIQUE

16 Rue Porte a Bateaux - 27540 Ivry-la-Bataille - FRANCE

Tel : 33 (0)2 32 22 35 05 - Fax : 33 (0)2 32 36 93 08

www.efe-sensor.com - infos@efe-sensor.com