

MTi 600 SERIES

IMU | VRU | AHRS | GNSS/INS



- ✓ Industrial grade, highly affordable, MEMS-based orientation sensor
- ✓ Full-featured sensor fusion algorithm with easy to use SDK
- ✓ 4 integration levels available: IMU, VRU, AHRS and GNSS/INS
- ✓ Native CAN interface and external GNSS receiver support



Product Overview

	MTi-610 IMU	MTi-620 VRU	MTi-630 AHRS	MTi-670 GNSS/INS
Calibrated sensor data	✓	✓	✓	✓
Roll/Pitch		0.2°	0.2°	0.2°
Yaw		✓	1.5°	1°
GNSS interface				✓

Xsens





Sensor specifications

	Gyroscopes	Accelerometers
Standard full range	+/- 2000 °/s	+/- 10 g
Initial bias error	-	5 mg
In-run bias stability	8 %/h	15 µg
Bandwidth (-3 dB)	520 Hz	500 Hz
Noise density	0.007 °/s/√Hz	60 µg/√Hz
g-sensitivity (calibrated)	0.001 °/s/g	N/A
Non-orthogonality	0.05 °	0.05 °
Non-linearity	0.1%	0.1%

	Magnetometer
Standard full range	+/- 8 G
Total RMS noise	1 mG
Non-linearity	0.2%
Resolution	0.25 mG

System specifications

Input voltage	4.5 to 24V	Interfaces	CAN/RS232/UART
Typical power consumption	TBD	Sync options	SyncIn, SyncOut, ClockSync
IP-rating	IP51	Interface protocol	Xbus, ASCII (NMEA) or CAN
Temperature (in use)	-40 to 85 °C	Mounting orientation	No restriction, full 360° in all axes
Casing material	PC-ABS	Built-in self test (BIT)	Gyroscopes, accelerometers, magnetometer
Clock drift	10 ppm or external reference	MTBF	TBD
Output frequency	1kHz, 400Hz SDI	External GNSS receiver support	UBX protocol (MAX M8) and NMEA input



MTi 600-series Development Kit:
MTi, Development board, UART2USB, USB cable
(MTi-670-DK: GNSS daughter card, GNSS antenna)



MTi encased:
28x31.5x13 mm, <10g,
16-pins header

Xsens

