



## **PTSSP6-G**

### **STAINLESS STEEL SINGLE POINT**


- Fully sealed
- C3 accuracy class
- Stainless steel for protection
- For platform and retail scales
- Suits 600mm x 600mm platform



#### **Models**

| <b>Capacity</b> | <b>Order</b>   | <b>Weight (kg)</b> |
|-----------------|----------------|--------------------|
| 100kg           | SPM0100S06GXXX | 4.5                |
| 150kg           | SPM0150S06GXXX | 4.5                |
| 200kg           | SPM0200S06GXXX | 4.5                |
| 250kg           | SPM0250S06GXXX | 4.5                |
| 300kg           | SPM0300S06GXXX | 4.5                |
| 500kg           | SPM0500S06GXXX | 4.5                |
| 600kg           | SPM0600S06GXXX | 4.5                |

NOTE: dimensions are in mm(in.).



#### **Specifications**

|                                       |                 |                               |                           |
|---------------------------------------|-----------------|-------------------------------|---------------------------|
| Signal Output at Capacity.....        | 2±0.2 mV/V      | Service Load.....             | 100% Capacity             |
| Linearity Error.....                  | < 0.017% FSO    | Safe Load.....                | 150% Capacity             |
| Non-Repeatability.....                | < 0.010% FSO    | Ultimate Load.....            | 300% Capacity             |
| Combined Error.....                   | < 0.020% FSO    | Input Resistance.....         | 409Ω ± 6Ω                 |
| Off Centre Load Error.....            | < 0.020% FSO    | Output Resistance.....        | 350Ω ± 3Ω                 |
| Creep/(30 mins.).....                 | < 0.015% FSO    | Insulation Resistance.....    | > 5000 MΩ (@50 VDC)       |
| Zero Balance.....                     | < 2.0% Capacity | Excitation Voltage(Rec).....  | 5~12 V AC/DC              |
| Temperature Effect on Span/(10C)..... | < 0.014% FSO    | Excitation Voltage(Max.)..... | 18 V AC/DC                |
| Temperature Effect on Zero/(10C)..... | < 0.017% FSO    | Cable.....                    | 3m long, Ø6.3mm           |
| Operating Temperature Range.....      | -35 ~ +65 C     | .....                         | 6-wire shielded PVC cable |
| Compensated Temperature Range.....    | -10 ~ +40 C     | Material.....                 | 17-4PH Stainless steel    |
| Storage Temperature Range.....        | -50 ~ 85 C      | Sealing.....                  | IP65                      |

#### **Wiring Connections**

|                     |       |                |        |                 |       |
|---------------------|-------|----------------|--------|-----------------|-------|
| Excitation +ve..... | Red   | Sense +ve..... | Blue   | Signal +ve..... | Green |
| Excitation -ve..... | Black | Sense -ve..... | Yellow | Signal -ve..... | White |

R81030



<http://www.pt-global.com>

