



PTSSP6-Q

STAINLESS STEEL SINGLE POINT


- Fully sealed IP67
- C3 accuracy class
- Stainless Steel for protection
- For platform and retail scales
- Suits 400mm x 400mm platform



Models

Capacity	Order	Weight (kg)
200kg	SPM0200S06QXXX	1.50
250kg	SPM0250S06QXXX	1.50

NOTE: dimensions are in mm(in.).



Specifications

Signal Output at Capacity.....	2±0.2 mV/V	Service Load.....	100% Capacity
Linearity Error.....	< 0.017% FSO	Safe Load.....	150% Capacity
Non-Repeatability.....	< 0.010% FSO	Ultimate Load.....	300% Capacity
Combined Error.....	< 0.020% FSO	Input Resistance.....	383Ω ± 4Ω
Off Centre Load Error.....	< 0.020% FSO	Output Resistance.....	350Ω ± 3.5Ω
Creep/(30 mins.).....	< 0.020% FSO	Insulation Resistance.....	> 5000 MΩ (@50 VDC)
Zero Balance.....	< 1% Capacity	Excitation Voltage(Rec).....	5~12 V AC/DC
Temperature Effect on Span/(10C).....	< 0.014% FSO	Excitation Voltage(Max.).....	18 V AC/DC
Temperature Effect on Zero/(10C).....	< 0.017% FSO	Cable.....	1.5m long, Ø5.1
Operating Temperature Range.....	-35 ~ +65 C	Material.....	6-wire shielded PU cable
Compensated Temperature Range.....	-10 ~ +40 C	Sealing.....	17-4ph Stainless steel
Storage Temperature Range.....	-50 ~ 85 C		IP67

Wiring Connections

Excitation +ve.....	Green	Sense +ve.....	Blue	Signal +ve.....	Red
Excitation -ve.....	Black	Sense -ve.....	Brown	Signal -ve.....	White

R81030



<http://www.pt-global.com>

