















Strain Gauge - Tri-Axial

GAGE PATTERN				GAGE DESIGNATION		RES.IN OHMS	LEAD WIRES OPTIONS AVAILABLE
Actual size shown. Enlarged when necessary for definition.				Insert desired S-T-C number in spaces marked XX. (9, 11, 16, 23, 27) ppm			
Unit: millimeter							
TS2-120 <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  1X </div> <div style="text-align: center;">  3X </div> </div>				Matrix Length: 5.56 Matrix Width: 5.56			
GAGE LENGTH	GRID WIDTH	OVERALL LENGTH	OVERALL WIDTH	TS2-120-PC-XX		120	E,L,LE,PXX
2.00	1.14	3.96	3.96				
TS2-350 <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  1X </div> <div style="text-align: center;">  3X </div> </div>				Matrix Length: 5.56 Matrix Width: 5.56			
GAGE LENGTH	GRID WIDTH	OVERALL LENGTH	OVERALL WIDTH	TS2-350-PC-XX		350	E,L,LE,PXX
2.00	1.14	3.96	3.96				
TS3-120 <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  1X </div> <div style="text-align: center;">  2X </div> </div>				Matrix Length: 7.13 Matrix Width: 7.13			
GAGE LENGTH	GRID WIDTH	OVERALL LENGTH	OVERALL WIDTH	TS3-120-PC-XX		120	E,L,LE,PXX
3.00	1.70	5.61	5.61				
TS3-350 <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  1X </div> <div style="text-align: center;">  2X </div> </div>				Matrix Length: 7.13 Matrix Width: 7.13			
GAGE LENGTH	GRID WIDTH	OVERALL LENGTH	OVERALL WIDTH	TS3-350-PC-XX		350	E,L,LE,PXX
3.00	1.70	5.61	5.61				

Strain Gauge - Tri-Axial

GAGE PATTERN <small>Actual size shown. Enlarged when necessary for definition.</small>				GAGE DESIGNATION <small>Insert desired S-T-C number in spaces marked XX. (0, 5, 9, 11, 17, 23) ppm</small>	RES.IN OHMS	ENCAPSULATION and LEAD WIRES OPTIONS AVAILABLE
<small>Unit: millimeter</small>						
TR5-120I <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  1X </div> <div style="text-align: center;">  1.5X </div> </div>				Matrix Length: 14.00 Matrix Width: 14.00		
GAGE LENGTH	GRID WIDTH	OVERALL LENGTH	OVERALL WIDTH	TR5-120I-PC-XX	120	E,L,LE,PXX
4.25	3.19	11.83	11.83			
TS7-120 <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  1X </div> <div style="text-align: center;">  1.5X </div> </div>				Matrix Length: 11.39 Matrix Width: 11.39		
GAGE LENGTH	GRID WIDTH	OVERALL LENGTH	OVERALL WIDTH	TS7-120-PC-XX	120	E,L,LE,PXX
6.50	3.13	9.50	9.50			
TS7-350 <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  1X </div> <div style="text-align: center;">  1.5X </div> </div>				Matrix Length: 11.39 Matrix Width: 11.39		
GAGE LENGTH	GRID WIDTH	OVERALL LENGTH	OVERALL WIDTH	TS7-350-PC-XX	350	E,L,LE,PXX
6.50	3.13	9.50	9.50			